



אלמור פיברגלס

יבוא יצוא 1996 בע"מ

ILK-738 DARKBLACK PIGMENT PASTE (RAL-9005)

ILKALEM polyester-based pigment pastes are produced with the highest quality pigments. These smooth pigment pastes rapidly blend and distribute homogenously when stirred into the liquid resin. Opacity is obtained at various pigment paste percentages, depending on the material's thickness and color.

Description / Properties

Appearance	Pigmented paste
Odor	Mild resin odor
Powder pigment %	41
Density at 20 °C, g/cm ³	1.70
Viscosity at 20°C,	Min. 10,000
Application %	2 - 15
Flash point	Non flamm
Solubility in water	Insolube

Storage life :

Minimum 36 months (20°C in darkness). Avoid exposure to heat sources such as direct sunlight, steam pipes, heaters, etc. and keep in closed containers. Do not stir the pigment paste with a used stick (styrene, polyester, gelcoat or similar chemicals) due to the fact that it may become unusable before shelf-life. Rotate stock to ensure use within 36 months.

Packing :

25 Kg net, 26.5 Kg gross, tin buckets,
5 Kg net, 5.5 Kg gross, tin buckets,

Field of application : Colouring of unsaturated polyester resins, gelcoats and similar resins.